



ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	5W
MAX.SWITCHING CURRENT	DC 0.4A / AC 0.28A
MAX.SWITCHING VOLTAGE	125VAC 175VDC

△					
△					
△					
△					
△	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED

DESIGN DATA					
CODE	N/A				
UNIT	mm				
KIND OF FLUID	—				
PRESS.	DESIGN	Max. 10	Kg/Cm ²		
	OPERATING	—	Kg/Cm ²		
TEMP. (SENSOR)	DESIGN	−20 ~ 60	°C		
	OPERATING	—	°C		
TEMP. (ELECTRONICS)	DESIGN	−20 ~ 60	°C		
	OPERATING	—	°C		
SP.GR.	MORE THAN 0.74				
VISCOSITY	10 P / 1 Pa.s				
ENCLOSURE	WEATHER PROOF				
FLANGE SIZE	JIS 10K 80A FF				
FLOAT TYPE	ø49x50L				
TAG NO.	L	L1	L2	L3	L4

NOTES

1. () Dimensions are reference dimensions.

REVISION

6	FLOAT	316SS	2		
5	FLOAT STOPPER	304SS	4		
4	STEM	304SS	1	ø13.8	
3	FLANGE	304SS	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL					
CUSTOMER					
PROJECT					
TITLE					
TITLE					
MANUFACTURER					
SCALE					
SCALE					
REV.					
REV.					