



WIRING DIAGRAM

ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	50W / 70VA
MAX.SWITCHING CURRENT	0.5A
MAX.SWITCHING VOLTAGE	350VDC 300VAC

△					
△					
△					
△					
△	FOR APPROVAL	2017.11.30			
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED

DESIGN DATA						
CODE		N/A				
UNIT		mm				
KIND OF FLUID		-				
PRESS.	DESIGN	Max. 10		Kg/Cm <sup>2</sup>		
	OPERATING	-		Kg/Cm <sup>2</sup>		
TEMP. (SENSOR)	DESIGN	-20 ~ 60		°C		
	OPERATING	-		°C		
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60		°C		
	OPERATING	-		°C		
SP.GR.		MORE THAN 0.74				
VISCOSITY		10 P / 1 Pa.s				
ENCLOSURE		WEATHER PROOF				
FLANGE SIZE		N/A				
FLANGE DIMENSION		N/A				
FLOAT TYPE		ø49x50L				
TAG NO.		L	L1	L2	L3	L4

NOTES  
1. ( ) Dimensions are reference dimensions.

REVISION

6	FLOAT	316SS	1		
5	FLOAT STOPPER	304SS	2		
4	STEM	304SS	1	ø13.8	
3	SOCKET	304SS	1	PT 2"	
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL					
CUSTOMER					
PROJECT					
TITLE					
MANUFACTURER					
SCALE					
DWG NO.					
REV.					