



ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	5W
MAX.SWITCHING CURRENT	DC 0.4A / AC 0.28A
MAX.SWITCHING VOLTAGE	125VAC 175VDC

△					
△					
△					
△	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED

DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	—	
PRESS.	DESIGN	Max. 10 Kg/Cm ²
TEMP.	OPERATING	—
(SENSOR)	DESIGN	—20 ~ 60 °C
TEMP.	OPERATING	—20 ~ 60 °C
(ELECTRONICS)	DESIGN	—
SP.GR.	OPERATING	—
VISCOSITY	MORE THAN 0.74	
ENCLOSURE	10 P / 1 Pa.s	
FLANGE SIZE	WEATHER PROOF	
FLOAT TYPE	JIS 10K 80A FF	
TAG NO.	L	L1 L2 L3 L4

NOTES

1. () Dimensions are reference dimensions.

REVISION

6	FLOAT	316SS	3		
5	FLOAT STOPPER	304SS	6		
4	STEM	304SS	1	ø13.8	
3	FLANGE	304SS	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—

TITLE
ST-3S-C-1-A-1-D-1-B-3
ASSEMBLY DRAWING

MANUFACTURER

Seojin Instech Co., Ltd.

SCALE	DATE	REV.
N/S	SJ-M003-DWG-AP016	