



WIRING DIAGRAM

ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	50W / 70VA
MAX.SWITCHING CURRENT	0.5A
MAX.SWITCHING VOLTAGE	350VDC 300VAC

△					
△					
△					
△					
△	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED

DESIGN DATA

CODE	N/A							
UNIT	mm							
KIND OF FLUID	-							
PRESS.	DESIGN	Max. 5	Kg/Cm ²					
	OPERATING	-	Kg/Cm ²					
TEMP. (SENSOR)	DESIGN	-20 ~ 60	°C					
	OPERATING	-	°C					
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60	°C					
	OPERATING	-	°C					
SP.GR.	MORE THAN 0.62							
VISCOSITY	10 P / 1 Pa.s							
ENCLOSURE	WEATHER PROOF							
FLANGE SIZE	JIS 10K 80A FF							
FLOAT TYPE	ø75x80L							
TAG NO.	L	L1	L2	L3	L4			

NOTES

1. () Dimensions are reference dimensions.

REVISION

6	FLOAT	PVC	2		
5	FLOAT STOPPER	PVC	4		
4	STEM	304SS+PVC	1	ø22	
3	FLANGE	PVC	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		

NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK
BILL OF MATERIAL					
CUSTOMER					
PROJECT					
TITLE					
ST-2S-B-1-C-1-A-1-B-3					
ASSEMBLY DRAWING					
MANUFACTURER					
SeoJin Instech Co., Ltd.					
SCALE	ERP CODE	Work Order No.			REV.
N/S	△	-	-		△
DWG NO.	SJ-M003-DWG-AP011				