



WIRING DIAGRAM

ELECTRIC RATING (RESISTIVE)	
MAX.CONTACT RATING	50W / 70VA
MAX.SWITCHING CURRENT	0.5A
MAX.SWITCHING VOLTAGE	350VDC 300VAC

△					
△					
△					
△					
△	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED

DESIGN DATA

CODE	N/A				
UNIT	mm				
KIND OF FLUID	-				
PRESS.	DESIGN	Max. 5			Kg/Cm ²
	OPERATING	-			Kg/Cm ²
TEMP. (SENSOR)	DESIGN	-20 ~ 60			°C
	OPERATING	-			°C
TEMP. (ELECTRONICS)	DESIGN	-20 ~ 60			°C
	OPERATING	-			°C
SP.GR.	MORE THAN 0.62				
VISCOSITY	10 P / 1 Pa.s				
ENCLOSURE	WEATHER PROOF				
FLANGE SIZE	JIS 10K 80A FF				
FLOAT TYPE	ø75x80L				
TAG NO.	L	L1	L2	L3	L4

NOTES

1. () Dimensions are reference dimensions.

REVISION

6	FLOAT	PVC	1		
5	FLOAT STOPPER	PVC	2		
4	STEM	304SS+PVC	1	ø22	
3	FLANGE	PVC	1		
2	HOUSING	ADC12	1		
1	COVER	ADC12	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-				
PROJECT	-				
TITLE	FLOAT TYPE LEVEL SWITCH ST-1S-A-1-C-1-A-1-B-3 ASSEMBLY DRAWING				
MANUFACTURER	SeoJIn Instech Co.,Ltd.				
SCALE	ERP CODE	Work Order No.	REV.		
N/S	DWG NO.	SJ-M003-DWG-AP005	△		