

Level instruments

Continuous level measurement - Ultrasonic controllers

HydroRanger 200

Overview



HydroRanger 200 is an ultrasonic level controller for up to six pumps and provides control, differential control and open channel flow monitoring.

Benefits

- Monitors wet wells, weirs and flumes
- Digital communications with built-in Modbus RTU via RS-485
- Compatible with SmartLinx system and SIMATIC PDM configuration software
- Single or dual point level monitoring
- 6 relay (standard), 1 or 3 relay (optional)
- Auto False-Echo Suppression for fixed obstruction avoidance
- Anti-grease ring/tide mark buildup
- Differential amplifier transceiver for common mode noise rejection and improved signal-to-noise ratio
- Wall and panel mounting options

Application

For water authorities, municipal water, and wastewater plants, HydroRanger 200 is an economical, low-maintenance solution delivering control efficiency and productivity needed to meet today's exacting standards. It offers single point monitoring with all models, and optional dual-point monitoring with 6 relay model. As well, it has digital communications with built-in Modbus RTU via RS-485.

The standard 6 relay HydroRanger 200 will monitor open channel flow and features more advanced relay alarming and pump control functions as well as volume conversion. It is compatible with SIMATIC PDM, allowing for PC configuration and setup.

Sonic Intelligence[®] advanced echo-processing software provides increased reading reliability. The optional 1 or 3 relay models provide accurate level measurement functions only; these two models do not provide open channel flow, differential level measurement or volume conversion functions.

HydroRanger 200 uses proven continuous ultrasonic echo ranging technology to monitor water and wastewater of any consistency up to 15 m (50 ft) in depth. Achievable resolution is 0.1% with accuracy to 0.25% of range. Unlike contacting devices, HydroRanger 200 is immune to problems caused by suspended solids, harsh corrosives, grease or silt in the effluent, reducing downtime.

- Key Applications: wet wells, flumes/weirs, bar screen control

Level instruments

Continuous level measurement - Ultrasonic controllers

HydroRanger 200

Technical specifications

Mode of Operation

Measuring principle	Ultrasonic level measurement
Measuring range	0.3 to 15 m (1 to 50 ft), transducer dependent
Measuring points	1 or 2

Input

Analog	0 to 20 mA or 4 to 20 mA, from alternate device, scaleable (6 relay model)
Discrete	10 to 50 V DC switching level Logical 0 = < 0.5 V DC Logical 1 = 10 to 50 V DC Max. 3 mA

Output

Echomax [®] Transducer	44 kHz
Ultrasonic transducer	Compatible transducers: ST-H and Echomax series XPS-10/10F, XPS 15/15F, XCT-8, XCT-12 and XRS-5
Relays ¹⁾	Rating 5 A at 250 V AC, non-inductive
- Model with 1 relay ²⁾	1 SPST Form A
- Model with 3 relays ²⁾	2 SPST Form A/1 SPDT Form C
- Model with 6 relays	4 SPST Form A/2 SPDT Form C
mA output	0 to 20 mA or 4 to 20 mA
• Max. load	750 Ω, isolated
• Resolution	0.1 % of range

Accuracy

Error in measurement	0.25% of range or 6 mm (0.24"), whichever is greater
Resolution	0.1% of measuring range or 2 mm (0.08"), whichever is greater ³⁾
Temperature compensation	<ul style="list-style-type: none"> • -50 to +150 °C (-58 to +302 °F) • Integral temperature sensor in transducer • External TS-3 temperature sensor (optional) • Programmable fixed temperature values

Rated operating conditions

<u>Installation conditions</u>	
Location	indoor / outdoor
Installation category	II
Pollution degree	4
<u>Ambient conditions</u>	
Ambient temperature (enclosure)	-20 to +50 °C (-4 to +122 °F)

Design

Weight	
• Wall mount	1.37 kg (3.02 lbs)
• Panel mount	1.50 kg (3.31 lbs)
Material (enclosure)	Polycarbonate
Degree of protection (enclosure)	
• Wall mount	IP65/Type 4X/NEMA 4X
• Panel mount	IP54/Type 3/NEMA 3

Cable

Transducer and mA output signal	2-core copper conductor, twisted, shielded, 300 Vrms, 0.82 mm ² (18 AWG), Belden [®] 8760 or equivalent is acceptable
Max. separation between transducer and transceiver	365 m (1200 ft)

Displays and controls

Programming	100 x 40 mm (4 x 1.5") multi-block LCD with backlighting
Programming	Programming using handheld programmer or via PC with SIMATIC PDM software

Power supply⁴⁾

AC version	100 to 230 V AC ± 15%, 50/60 Hz, 36 VA (17 W)
DC version	12 to 30 V DC (20 W)

Certificates and approvals

- CE, C-TICK⁵⁾
- Lloyd's Register of Shipping
- ABS Type Approval
- FM, CSA_{US/C}, UL listed
- CSA_{US/C} Class I, Div. 2, Groups A, B, C and D, Class II, Div. 2, Groups F and G, Class III (wall mount only)
- MCERTS Class 1 approved for Open Channel Flow

Communication

- RS-232 with Modbus RTU or ASCII via RJ-11 connector
- RS-485 with Modbus RTU or ASCII via terminal blocks
- Optional: SmartLinx[®] cards for
 - PROFIBUS DP
 - DeviceNet[™]
 - Allen-Bradley[®] Remote I/O

¹⁾ All relays certified for use with equipment that fails in a state at or under the rated maximums of the relays

²⁾ This model is level control only; no open channel flow, differential level or volume conversion functions

³⁾ Program range is defined as the empty distance to the face of the transducer plus any range extension

⁴⁾ Maximum power consumption is listed

⁵⁾ EMC performance available upon request

Level instruments

Continuous level measurement - Ultrasonic controllers

HydroRanger 200

Selection and Ordering data	Order No.
Siemens HydroRanger 200 Ultrasonic level controller for up to six pumps that provides control, differential control and open channel flow monitoring. The HydroRanger 200 is also available as a level measurement controller only. Select option from model code below.	C) 7ML5034-
Mounting Wall mount, standard enclosure Wall mount, 4 entries, 4 M20 cable glands included Panel mount ¹⁾	1 2 3
Power supply 100 to 230 V AC 12 to 30 V DC	A B
Number of measurement points Single point model, 6 relays Dual point model, 6 relays Single point model, level only, 1 relay ²⁾ Single point model, level only, 3 relays ²⁾	A B C D
Communication (SmartLinx) Without module SmartLinx® Allen-Bradley® Remote I/O module SmartLinx PROFIBUS DP module SmartLinx DeviceNet™ module See SmartLinx product page 5/301 for more information.	0 1 2 3
Approvals General Purpose CE, FM, CSA _{USC} , UL listed, C-TICK CSA Class I, Div. 2, Groups A, B, C and D; Class II, Div 2, Groups F and G; Class III (for wall mount applications only)	1 2
Further designs Please add "-Z" to Order No. and specify Order code(s).	Order code
Stainless steel tag [69 x 50 mm (2.71 x 1.97")]: Measuring-point number/identification (max. 16 characters) specify in plain text	Y15
Instruction manual English French German Note: The instruction manual should be ordered as a separate line on the order. This device is shipped with the Siemens Milltronics manual CD containing the complete Quick Start and instruction manual library.	Order No. C) 7ML1998-5FC02 C) 7ML1998-5FC11 C) 7ML1998-5FC32
Other instruction manuals SmartLinx Allen-Bradley Remote I/O, English SmartLinx PROFIBUS DP, English SmartLinx PROFIBUS DP, German SmartLinx PROFIBUS DP, French SmartLinx DeviceNet, English Note: The appropriate SmartLinx instruction manual should be ordered as a separate line on the order.	C) 7ML1998-1AP03 C) 7ML1998-1AQ03 C) 7ML1998-1AQ33 C) 7ML1998-1AQ12 C) 7ML1998-1BH02

Selection and Ordering data	Order No.
Siemens HydroRanger 200 Ultrasonic level controller for up to six pumps that provides control, differential control and open channel flow monitoring. The HydroRanger 200 is also available as a level measurement controller only. Select option from model code below.	C) 7ML5034-
Accessories Handheld programmer Tag, stainless steel, 12 x 45 mm (0.47 x 1.77"), one text line, suitable for enclosure TS-3 Temperature Sensor - see TS-3 on page 5/186 SITRANS RD100 Remote display - see RD100 on page 5/304 SITRANS RD200 Remote display - see RD200 on page 5/306	7ML1830-2AK 7ML1930-1AC
Spare parts Power Supply Board (100 to 230 V AC) Power Supply Board (12 to 30 V DC) Display Board See SmartLinx product page 5/301 for more information.	C) 7ML1830-1MD C) 7ML1830-1ME C) 7ML1830-1MF

¹⁾ Available with approval option 1 only

²⁾ This model is level control only; no open channel flow, differential level, or volume conversion functions

C) Subject to export regulations AL: N, ECCN: EAR99

Level instruments

Continuous level measurement - Ultrasonic controllers

HydroRanger 200

Selection and Ordering data

Order No.

Milltronics HydroRanger 200

Ultrasonic level controller for up to six pumps that provides control, differential control and open channel flow monitoring. The HydroRanger 200 is also available as a level measurement controller only. Select option from model code below.

L) **7ML1034-**

Mounting

Wall mount, standard enclosure

Wall mount, 4 entries, 4 M20 cable glands included

Panel mount¹⁾1
2
3

Power supply

100 to 230 V AC

12 to 30 V DC

A
B

Communication (SmartLinX)

Without module

SmartLinX[®] Allen-Bradley[®] Remote I/O module

SmartLinX PROFIBUS DP module

SmartLinX DeviceNet[™] module

See SmartLinX product page 5/301 for more information.

A
B
C
D

Approvals

General Purpose CE, FM, CSA_{USC}, UL listed, C-TICK

CSA Class I, Div. 2, Groups A, B, C and D; Class II, Div 2, Groups F and G; Class III (for wall mount applications only)

1
2

Number of measurement points

Single point model, 6 relays

Dual point model, 6 relays

Single point model, level only, 1 relay²⁾Single point model, level only, 3 relays²⁾1
2
3
4

Further designs

Order code

Please add "**-Z**" to Order No. and specify Order code(s).

Stainless steel tag [69 x 50 mm (2.71 x 1.97")]: Measuring-point number/identification (max. 16 characters) specify in plain text

Y15

Instruction manual

Order No.

English

C) **7ML1998-1FC05**

French

C) **7ML1998-1FC14**

German

C) **7ML1998-1FC34**

Note: The instruction manual should be ordered as a separate line on the order.

This device is shipped with the Siemens Milltronics manual CD containing the complete ATEX Quick Start and instruction manual library.

Other instruction manuals

SmartLinX Allen-Bradley Remote I/O, English

C) **7ML1998-1AP03**

SmartLinX PROFIBUS DP, English

C) **7ML1998-1AQ03**

SmartLinX PROFIBUS DP, German

C) **7ML1998-1AQ33**

SmartLinX PROFIBUS DP, French

C) **7ML1998-1AQ12**

SmartLinX DeviceNet, English

C) **7ML1998-1BH02**

Note: The appropriate SmartLinX instruction manual should be ordered as a separate line on the order.

Selection and Ordering data

Order No.

Milltronics HydroRanger 200

Ultrasonic level controller for up to six pumps that provides control, differential control and open channel flow monitoring. The HydroRanger 200 is also available as a level measurement controller only. Select option from model code below.

L) **7ML1034-**

Accessories

Handheld programmer

Tag, stainless steel, 12 x 45 mm (0.47 x 1.77"), one text line, suitable for enclosure

7ML1830-2AM
7ML1930-1AC

TS-3 Temperature Sensor -

see TS-3 on page 5/186

SITRANS RD100 Remote display -

see RD100 on page 5/304

SITRANS RD200 Remote display -

see RD200 on page 5/306

Spare parts

Power Supply Board (100 to 230 V AC)

C) **7ML1830-1MD**

Power Supply Board (12 to 30 V DC)

C) **7ML1830-1ME**

Display Board

C) **7ML1830-1MF**

See SmartLinX product page 5/301 for more information.

1) Available with approval option 1 only

2) This model is level control only; no open channel flow, differential level, or volume conversion functions

C) Subject to export regulations AL: N, ECCN: EAR99

L) Subject to export regulations AL: N, ECCN: 3A991X

®Modbus is a registered trademark of Schneider Electric.

®Belden is a registered trademark of Belden Wire and Cable Company.

®Allen-Bradley is a registered trademark of Rockwell Automation.


™DeviceNet is a trademark of Open DeviceNet Vendor Association (ODVA)

Level instruments

Continuous level measurement - Ultrasonic controllers


HydroRanger 200

Dimensional drawings



HydroRanger 200 dimensions

Schematics



HydroRanger 200 connections